

RADIOTELEPHONE5 Background of the Invention

This invention relates to a radiotelephone, and in particular a removable housing for a radiotelephone.

10 It has become desirable for users of radiotelephones to replace a broken or scratched housing of a radiotelephone easily without requiring any special training or tools. Also, users of radiotelephones may want to change the appearance of their radiotelephone by replacing its housing with another of a different appearance.

15 Known removable front covers for radiotelephones have a latching element formed from the front cover moulding that engages with an aperture on a rear housing of the radiotelephone. The removal of this type of front cover is a two handed operation requiring a user to, first, use one hand to disengage the latching element from the rear housing aperture then, due to the frictional
20 force that exists between the latching element and the rear housing, use a second hand to remove the front cover from the rear housing.

It is desirable to improve this situation.

25 Summary of the Invention

According to an aspect of the present invention there is provided an electronic radiotelephone comprising a first and second housing for housing the electronic components of the radiotelephone; the first housing having an element with an operating surface and a formation arranged to co-operate
30 with a complementary formation on the second housing for releasably attaching the first housing to the second housing; the element being movable

09852630-054101

between a first and a second position such that when the element is in the first position the formation and complementary formation are arranged to co-operate to allow the first housing to be coupled to the second housing and when in the second position allow the second housing to be removed from the first housing; the element being resiliently biased into the first position and arranged to allow a user to urge the element, via the operating surface, into the second position during the removal of the second housing from the first housing, thereby allowing the second housing to be removed from the first housing without interference from the element.

10

This provides the advantage of allowing the second housing to be removed from the first housing without interference from the first housing, thereby allowing easy removal of the second housing from the first housing.

15 Preferably the first housing is presented away from a user during operation of the radiotelephone and the second housing is presented towards a user during operation of the radiotelephone.

Suitably the radiotelephone further comprises retaining means for retaining the electronic components of the radiotelephone to the first housing.

20

Preferably the element is a flexible hinge.

Most preferably the radiotelephone further comprises means for urging the second housing away from the first housing to aid the removal of the second housing from the first housing.

25

This allows the second housing to be moved away from the first housing on movement of the element from the first to the second position without requiring a user to handle the second housing. This allows the second housing to be removed from the first housing in response to a single operation.

30

09852630 051101

Brief Description of the Drawings

For a better understanding of the present invention and to understand how the same may be brought into effect reference will now be made, by way of example only, to accompanying drawings, in which:-

5

Figure 1 shows a radiotelephone according to an embodiment of the present invention;

Figure 2 shows an exploded view of the radiotelephone of figure 1;

10

Figure 3 shows a cross-section through part of the housing of figure 1;

Figure 4a shows a cross-section through a second part of the housing of figure 1 with the front and rear housings attached;

15

Figure 4b shows a cross-section through a second part of the housing of figure 1 with the front and rear housings detached.

Detailed Description of the Invention

20 Figure 1 shows a radiotelephone 1 having a shell shaped first housing 2, otherwise referred to as a front cover, having a front wall 3 integral with side walls 4; a second housing 5, otherwise referred to as a rear cover, having a rear wall 6 integral with side walls 7; and an inner housing 8. Sandwiched between the front cover 2 and inner housing 8 is a keymat 9. The inner
25 housing 8 is coupled to the rear cover 5, as described below.

Figure 2 shows the mechanical structure of the radiotelephone 1. A keymat 9 is snapped on and off the inner side of the front cover 2. The main purpose of the keymat 9 is to act as an interface between the user and the functions of
30 the radiotelephone 1. The inner housing 8 comprises an inner cover 10, a main circuit board 11, a system connector 12, a dome sheet 13, a speaker 14, a microphone 16 and a liquid crystal display 15. The inner cover 10 is

5

10

15

20

25

30

30

cross-section in figure 3, has a lower section 27 and an upper section 28. The lower section 27 is coupled to the rear wall 6 of the rear cover 5 via an attachment stud 29. The release button 26 can be attached to the rear wall 6 by any suitable means, for example welding, riveting. The release button is a flexible hinge, whereby the resilient material allows the upper section 28 to pivot relative to the lower section 27.

The upper section 28 of the release button 26 is biased against the upper wall 18 of the rear cover 5. The upper section 28 comprises an operating portion 30 and a latching portion 31. The operating portion 30 projects outwardly to form an extended surface. The extended surface extends into the U shaped cut away on the upper wall 18 of the rear cover 5. The extended surface allows a user to apply pressure, via a user's finger or thumb, to the release button 26, thereby allowing a user to urge the upper section 28 of the release button 26 away from the upper wall 18. The extended surface, otherwise known as operating surface, has, substantially, the same contour as the surrounding upper wall of the rear cover.

The latching portion 31 is formed above the operating portion 30, relative to the rear wall 6. The latching portion 31 forms a ridge that is arranged to engage with a complementary lip 32 on the front cover 2, as described below.

The front wall 3 of the front cover 2 has a plurality of apertures 33 through which components inside the housings partially project. The apertures 33 can be provided for, for example, push button keys, a display device or a loudspeaker device/microphone device. The side-walls 4 are arranged to match the corresponding side walls 7 on the rear cover 5 when the rear and front covers are attached.

The lower end-wall 34, transverse to the longitudinal axis of the front cover, has a cut away section (not shown) for accommodating the upper part of the system connector 12. On either side of the cut away section, located on the

00552630.051101

inner side of the end wall 34, are attaching lugs (not shown) that co-operate with the corresponding grooves 25 on the rear cover 5 for coupling the first and rear covers, as described below.

- 5 The upper end-wall 36, transverse to the longitudinal axis of the front cover, has a U shaped cut away section 38 for accommodating the upper part of the operating surface of the release button 30. Located above the cut-away section, on the inner side of the end-wall 36 is a lip 32 that co-operates with the ridge on the latching portion 31 of the release button 26 for coupling the
- 10 front and rear covers, as described below.

- Figure 4a and 4b shows a modification to the above described radiotelephone in which a leaf spring 37 is coupled to the inside of the front wall 3 of the front cover 2. In addition, the leaf spring is located below a protective window 39, wherein the window 39 is for viewing the display 15. The leaf spring 37 is arranged to be compressed by the inner housing 8 when the front and rear covers are attached, as shown in figure 4a. The leaf spring 37 provides spring bias between the front and rear covers. The spring bias between the front and rear covers is provided transverse to the longitudinal axis of the covers to
- 15 allow the front cover 2 to be urged away from the rear cover 5 uniformly on a transverse plane, as shown in figure 4b. However, any type of spring may be used that urges the front cover away from the rear cover. Alternatively, however, the spring may be coupled to either the rear cover or inner housing and arranged to urge the front cover away from the rear cover when the front
- 20 and rear covers are attached.
- 25

- To attach the front cover 2 to the rear cover 5 the lugs (not shown) on the lower wall 34 of the front cover 2 are brought into contact with the grooves 25 on the lower wall 24 of the rear cover 5, as shown in figure 1, thereby allowing
- 30 the lugs to engage with grooves 25. The upper part of the front cover 2 is moved towards the upper part of the rear cover 5, as shown by direction A in figure 1, overcoming spring bias of spring 37 as spring 37 is urged against the

09852630 051101
T01150 05925860

15
Sub
al

inner housing 8. As the upper part of the front cover 2 is brought into contact with the upper part of the rear cover 5 the lip 32 is brought into contact with the latching portion 31 of the release button 26. The lip 32 and latching portion 32 of the release button 26 are arranged so that on urging the lip 32 and latching portion 31 together the lip 32 causes the release button 26 to be urged inwards, away from the upper side wall 18 of the rear cover 5, until the lip 32 enters the ridge on the latching portion 31 of the release button 26, thereby latching the front cover 2 to the rear cover 5. Alternatively, a user may urge the release button 26 away from the upper side wall 18 of the rear cover 5 while bringing the front and rear covers together, thereby coupling, on release of the release button 26, the front and rear covers.

To remove the front cover 2 from the rear cover 5 the release button 26 is urged away from the upper side wall 18 of the rear cover 5, typically using a user's finger or thumb, thereby releasing contact between the lip 32 and release button 26. The spring bias of spring 37 urges the upper portion of the front cover 2 away from the upper portion of the rear cover 5 to allow the front cover 2 to be removed from the rear cover 5.

The present invention may include any novel feature or combination of features disclosed herein either explicitly or implicitly or any generalisation thereof irrespective of whether or not it relates to the presently claimed invention or mitigates any or all of the problems addressed.

In view of the foregoing description it will be evident to a person skilled in the art that various modifications may be made within the scope of the invention. The applicant hereby gives notice that new claims may be formulated to such features during prosecution of this application or of any such further application derived therefrom. For example, it will be appreciated that the release button 26 may be formed from the rear cover 5 or a rubber seal may be used in place of a spring for urging the front cover away from the rear

00552630 051101

Sub
a2

Sub
a3

cover when the front and rear covers are attached, wherein the rubber seal may be coupled to either the front cover, the rear cover or the inner housing.

What is claimed is:

09852630 051101
TOTAL 09852630